

**STORM SERIES**

**YNS220C SPECIFICATIONS 200KVA**



Australian Design.  
Powered by



**GENERAL**

Model	YNS220C
Power Type	Diesel
Prime Power (kW/kVA)	160/200
Standby Power (kW/kVA)	176/220

**ENGINE**

Engine Make and Model	CUMMINGS 6CTAA8.3-G2
Engine Type	In-line
Engine Power (kW)	203
Fuel Consumption (L/h)*	45
Battery Type	Lead acid, 2 x 12V - 120AH
Aspiration	Turbo-charged, Air to Air aftercooled
Bore (mm) x Stroke (mm)	114 x 135
No. of Cylinders	6
Displacement (L)	14
Compression Ratio	18.0:1
Governor Type	Electronic Governor
Lubricating Oil Capacity (L)	23.8

\*Fuel Consumption is based on 100% load

**ALTERNATOR**

Model	YANAN SLG274H1
Frequency (Hz)	50
Rate Power (kW/kVA)	160/200
PowerFactor	0.8
Exciter Type	Self-excited
Voltage Regulator	AS440
Voltage Regulation	±1.0%
No. of Phases	3
Insulation	Class H
Protection	IP 21
Altitude (m)	1000

**UNIT**

Dimensions L x W x H (m)	3.8 x 1.3 x 2.05
Dry Weight (kg)	2890
Sound at 7m/dB	76

**STANDARD FEATURES**

- 50°C rated radiator
- Powder coated finish
- Double Muffler
- Emergency E stop
- State of the art control system
- ATS available

**ASSEMBLY**

The engine and alternator are closed coupled by means of an SAE flange. A full torsional analysis has been carried out to guarantee no harmful vibration will occur. Anti-vibration pads are affixed between engine alternator feet and base frame. Rubber diagonal isolators are specifically designed to reduce engine and alternator vibration and prevent distortion in the voltage and harmonic output of the generator. All iron and steel surfaces of the canopy fabrication have been sand blasted and then powder coated, which provides an excellent corrosion resistant surface.



**CONTROL SYSTEM**

Automatic stop/start, Data measurement, Alarm protection and remote control, remote measuring and remote communication; SG485 module must be fitted in. LCD display and it is easy and reliable to use.



**QUALITY STANDARDS**

Our generator sets are compliant with all the main standards, such as ISO8528, ISO14000, GB755, BS5000, VDE0530, ISO3046, IEC34-1, AS3000.

**WARRANTY POLICY**

12 months, 1200 hours as per generator. Generators Australia Pty Ltd Warranty Policy. All photos are for marketing purposes only.